



## Bunting Bearings, LLC



6001 Bearing 2D drawings and 3D CAD models

Fxm SKF, NSK, NTN, Koyo, , Timken NACHI  
 6001 6002 6003 6004 6201 6202 6203 6204 6301  
 6302 6303 6304 Zz 2RS C3 Deep Groove Ball  
 Bearing

Bearing No. 6001

Size	12x28x8 mm
Bore Diameter	12 mm
Outer Diameter	28 mm
Width	8 mm
d	12 mm
D	28 mm
B	8 mm
C	8 mm
r min.	0.3 mm
da min.	14 mm
Da max.	26 mm
ra max.	0.3 mm
Weight	0.023 Kg
Basic dynamic load rating (C)	5,1 kN
Basic static load rating (C0)	2,39 kN
(Grease) Lubrication Speed	27000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	12 mm
Outside Diameter	28 mm
Width	8 mm
Fillet Radius/Chamfer	0.3 mm



## Bunting Bearings, LLC

Dynamic Load Rating	5,100 N
Static Load Rating	2,390 N
Limiting Speed - Grease	28,000 rpm
Limiting Speed - Oil	32,000 rpm
Factor $f_0$	13.2
Radial Clearance	0.003 to 0.018 mm
da (min)	14 mm
Da (max)	26 mm
ra (max)	0.3 mm